





PTB-81, 111, 112

S = Standard
O = Optional

Specifications	PTB-81	PTB-111	PTB-112	S	O
Capacity	10K / 11,700 GVWR / 8700 Pay. 12K / 14,000 GVWR / 11,000 Pay. 15K / 17,500 GVWR / 14,000 Pay.	Same as PTB-81	22,000 GVWR/17,700 Pay. 25,980 GVWR/21,500 Pay. 30,000 GVWR/25,000 Pay.	x	x x x
Axles	10K General Duty Dexter 10KHD, 12K, 15K Dexter 10KHD – 15K avail. in Air brake	same	same	x	x x x
Tires	ST235/80R16 LR-E (10K & 12K) 215/75R17.5 LR-H (15K)	same	same	x	x
Wheels	16" x 6" dual (10K and 12K) 17.5" x 6.75" dual (15K)	same	same	x	
Length adjustments	20'/25'/30'	25'/32'/40'	25'/32'/40'	x	
Cargo area	39" x 83"	39" x 119"	39" x 119"	x	
	12 guage steel floor	same	same		x
	Tie down pockets	same	same		x
	Bedliner	same	same		x
Overall width	95"	same	same	x	
Front Bolster	45" tubular bolster 60" Wide w/lever lock stanchions 95" wide w/lever lock stanchions	same	same	x	x x x
Center/Rear Bolsters	5" double c-channel w/stanchions Heavy duty winch binders w/straps	same	same	x x	
Tongue and Hitch	6" x 4" extendable tongue with wear pads	8" x 4"	8" x 4"	x	
Hitch plate	6-position adjustable with 2 1/2" lunette eye 3" lunette eye	same	same	x	x
Jack	Binkley Model 48000 (12,000 lb. static load capacity) Full width jack handle extension for 95" bolster	same	same	x	x
Fenders	1/8" steel diamond tread plate One pair mud flaps	same	same	x x	
Galvanizing	Galvanizing option available	same	same		x
Light bar	25' Pole mounted w/6-way connect. Light bar is attached to the pole with an adjustable 1/4" chain and wingnut.	Same	same		x